

VB-S30D



Comprehensively protect your environment with a Canon PTZ minidome network camera.

The easy-to-install Full HD PTZ Minidome network security camera with new ultra-compact zoom lens technology. Ideal for indoor security and monitoring in businesses and venues.

Key features

- Discrete ultra-compact PTZ Minidome design
- Full HD at 30fps for detailed images
- CMOS sensor delivers high performance in low light
- 3.5x optical zoom (4x digital) with 77.7° wide Angle of View
- Pan, Tilt, Zoom (PTZ) capability to programmed pre-set positions
- Multi-streaming of MJPEG and H.264 video in Full HD or lower resolutions
- Direct recording/playback from MicroSD card (64GB)
- Comprehensive and intelligent in-built analytics
- Auto Smart Shade Control applies the ideal exposure for every environment
- ONVIF v2.2 and Profile S compliant
- Compact size: just 120mm in diameter and 54mm in height

DiGiC NET	SSC Auto Smart Shade Control	
Auto Day/Night	Camera Tampering Detection	Compact
FULL HD	MJPEG H.264 30 fps	Intelligent Function
Power Supply PoE	microSD	

VB-S30D

Specifications

CAMERA	
Image Sensor	1/4.85 type CMOS (primary colour filter)
Number of Effective Pixels	Approx. 2.1 million pixels
Scanning Method	Progressive
Lens	3.5x optical (4x digital zoom) lens with auto focus
Focal Length	2.25 (W) – 7.88 mm (T)*
Viewing Angle	Horizontal: 77.7° (W) – 20.7° (T) Vertical: 40.4° (W) – 11.6° (T)
Day/Night Switch	Auto/Manual
Min. Subject Illumination	Day Mode (colour): 0.95 lux (F1.4, shutter speed 1/30 sec., smart shade control off, 50IRE) 0.07 lux (F1.4, shutter speed 1/2 sec., smart shade control off, 50IRE) 0.025 lux (F1.4, shutter speed 1/2 sec., smart shade control on, 50IRE) Night Mode (monochrome): 0.5 lux (F1.4, shutter speed 1/30 sec., smart shade control off, 50IRE) 0.04 lux (F1.4, shutter speed 1/2 sec., smart shade control off, 50IRE) 0.015 lux (F1.4, shutter speed 1/2 sec., smart shade control on, 50IRE)
Shooting Distance (from front of lens)	Auto/One-shot AF/Manual/Fixed at infinity 0.3 m (12 in.) – infinity
Shutter Speed	1, 1/2, 1/4, 1/8, 1/15, 1/30, 1/60, 1/100, 1/120, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/16000 sec.
Exposure	Auto/Auto (Flickerless)/Auto (Shutter-priority AE)/Manual (Shutter Speed, Gain)
White Balance	Auto/Light Source (Daylight Fluorescent/White Fluorescent/Warm Fluorescent/Mercury Lamp/Sodium Lamp/Halogen Lamp)/ Manual (One-shot WB/R Gain/B Gain)
Metering Mode	Center-Weighted/Average/Spot
AGC Limit	Auto/Manual/Disable Auto: 3 levels (default setting) Manual: 7 levels [Brightens shaded areas of a video] 5 levels
Pan Angle Range	90° (ceiling-mounted position: -90° – 0°) [When the horizontal direction of the camera is 0°]
Tilt Angle Range	90° (ceiling-mounted position: -90° – 0°) [When the horizontal direction of the camera is 0°]
Moving Speed	Pan: Max. 120°/sec., Tilt: Max. 120°/sec.
SERVER	
Video Compression Method	JPEG, H.264
Video Quality	JPEG, H.264: 1920 x 1080, 960 x 540, 480 x 270, 1280 x 720, 640 x 360, 320 x 180, 1280 x 960, 640 x 480, 320 x 240
Frame Rate	JPEG, H.264: 5 levels JPEG: 0.1 – 30 fps H.264: 1/2/3/5/6/10/15/30 fps [Values represent streaming performance from the camera] [The frame rate may be reduced due to Viewer PCs specs, the number of clients accessing at the same time, network loads, video quality setting, type or movement of the subject or other reasons]
Max. Frame Rate	When streaming JPEG, H.264 (1920 x 1080): 30 fps When used in the following combinations: When streaming H.264(1) (1920 x 1080) and H.264(2) (all sizes) simultaneously: 15 fps When streaming H.264(1) (all sizes) and H.264(2) (1920 x 1080) simultaneously: 15 fps When streaming H.264(1) (1980 x 960) and H.264(2) (1980 x 960) simultaneously: 15 fps When streaming H.264(1) (1980 x 720) and H.264(2) (1980 x 720) simultaneously: 15 fps
I-Frame Interval	0.5/1/1.5/2/3/4/5 sec.
Simultaneous Client Access	Max. 30 Clients + 1 Admin Client [H.264: Max. 10 Clients]
Camera Control	Administrator, Authorised user, Guest user (level of control varies depending on user) Max. 50 user names and passwords registered for Authorised users
Encrypted Communications	User authority (user name and password), Host Access Restrictions (IPv4, IPv6)
IEEE 802.1X Protocol	SSL/TLS, IPsec (Auto Key Exchange/Manual) EAP-MD5, EAP-TLS, EAP-TTLS, EAP-PEAP
Audio Compression Method	IPv4: TCP/IP, UDP, HTTP, FTP, SNMP (MIB2), SMTP (Client), DHCP (Client), DNS (Client), ARP, ICMP, POP3, NTP, SMTP authentication, RTSP, WV-HTTP (Canon proprietary), ONVIF IPv6: TCP/IP, UDP, HTTP, FTP, SMTP (Client), DHCPv6 (Client), DNS (Client), ICMPv6, POP3, NTP, SMTP authentication, RTSP, WV-HTTP (Canon proprietary), ONVIF

* (W): maximum wide angle, (T): maximum telephoto

SERVER CONT.	
Audio Communication Method	Sound Transfer Protocol by Canon
Privacy Mask	Number of registration: Max. 8 places, Number of mask colours: 1 (select from 9 colours)
View Restriction	Available
Presets	Max. 20 positions
Intelligent Function	Video: Detection Types: moving object detection, abandoned object detection, removed object detection, camera tampering detection, and passing detection Detection Settings: Max. 15 Volume: Volume Detection
Event Trigger Type	External Device Input, Timer, Intelligent Function (Video), Intelligent Function (Volume)
Image Upload	FTP/HTTP/SMTP (email). Temporary storage memory in camera: Max. approx. 5 MB, Frame Rate: Max. 10 fps (JPEG), Max. 30 fps (H.264)
Event Notification	HTTP/SMTP (email)
On-Screen Display	Available
Daylight Saving Time	Number of registers: 4 Items to Reg.: Pan/Tilt/Zoom, Exposure, Smart Shade Control, Focus, White Balance, Image Quality Adjustment, Day/Night
Custom Settings	
APPLICATION	
Admin Tools	Camera-side: Admin Viewer, VB Viewer Client-side: RM-Lite Viewer Privacy Mask Setting Tool, Panorama Creation Tool, View Restriction Setting Tool, Preset Setting Tool, Intelligent Function Setting Tool, Log Viewer, Recorded Video Utility
Language	English/German/Spanish/French/Italian/Japanese
Operating Environment (PC specifications and OS does not apply to RM-Lite)	Recommended CPU: Intel Core i7-2600 Graphics Board: Not specified Memory: 2 GB or more Viewer Display: 1920 x 1080 or more OS: Windows Vista Ultimate/Business/Enterprise/Home Premium SP2 32/64-bit Windows 7 Ultimate/Professional/Enterprise/Home Premium SP1 32/64-bit Windows 8/Windows 8 Pro/Windows 8 Enterprise 32/64-bit Windows Server 2008 Standard SP2 32/64-bit Windows Server 2008 R2 Standard SP1 64-bit Windows Server 2012 Standard 64-bit Web Browser: Internet Explorer 8/9/10 32-bit Runtime Libraries: .NET Framework 3.5 SP1 [When using Internet Explorer 8/9] .NET Framework 4.5 [When using Internet Explorer 10]
INTERFACE	
Network Terminal	LAN x 1 (RJ45, 100Base-TX (auto/full-duplex/half-duplex))
Audio Input Terminal (common for LINE IN & MIC IN)	φ3.5 mm (φ0.14 in.) mini-jack connector (monaural) Switch LINE IN/MIC IN in the setting page LINE IN x 1 (connect to an amplifier microphone) or MIC IN x 1 (connect to a microphone w/o amplifier)
External Device I/O Terminal	Input x 1, Output x 1
Memory Card	microSD Memory Card, microSDHC Memory Card, microSDXC Memory Card Compatible Frame Rate: Max. 1 fps (JPEG), Max. 30 fps (H.264)
OTHER	
Operating Environment	Temperature: -10°C – +50°C (+14°F – +122°F) Humidity: 5% – 85% (without condensation)
Power Supply	PoE: PoE power supply via LAN connector (IEEE802.3af compliant) Max. 7.8W
Power Consumption	
Dimensions	(φ x H) φ120 x 54 mm (φ4.72 x 2.13 in.) [Excluding projections]
Weight	Approx. 270g (9.6 oz.)

All data is based on Canon standard testing methods except where indicated. Subject to change without notice.

TM and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.