Rapport -10HD/PRO

Multi-Format Input Monitor



Suitable for HD CCTV monitor in limited space and field monitor as well.

10.05", 16:9 widescreen aspect ratio without the quality loss than comes from scaling, altering an image to fit on a different screen size

Superb connectivity with various surveillance equipments and peripherals with the HD-SDI, CVBS, VGA ports. And the HDMI port also gives uncompressed high quality video.

White LED backlight ensures natural colors from camera, DVR or others.

VESA standard 4 holes on the back allows placing in car window or mounting to a wall.

Dust protection optical bonding glass with AR/AG coating.

Li-ion Polymer battery with 5000mA capacity runs 4 to 6 hours with battery.

User-friendly GUI and intuitive and stylishly designed touch controls on the top of the sturdy aluminum case.

USB port prepared for firmware update in case debugging or performance enhancement.


FEATURES

- . Built-in 10.05" High resolution LCD
- Multi Format Video Input HDMI, HD-SDI, VGA, CVBS
- · Auto detection input video formats
- 100% Digital Processing
- · White LED BacklightV
- · 4:3 and 16:9 screen aspect ratios
- · User friendly GUI(Grapic user interface)
- · Li-ion Polymer Battery with 5000 mAh capacity
- · Runs 4 to 6 hours with Battery
- · Optical Bonding Glass with AR/AG coating (Dust Protection)
- · VESA standard 4 holes on the back
- · Mount for in-car System
- · Flush Type Stand
- · Aluminum frame
- · Power supply included


SPECIFICATIONS

| MODEL | Rapport -10HD | | |
|-------------------------------|-------------------------|--|----------------------|
| | Current consumption | 1600mA (DC 12V ± 15%) | |
| Electronic characteristics | Battery | Li-ion Polymer Battery, 5000mAh/7.4V (Built-in) | |
| | Built-in battery | Charging | 8hours (charge only) |
| | | time | 10hours (Working) |
| | | Operating | 4~5 hours |
| VIDEO | HD-SDI | 1080p 24,25,30 | |
| | | 1080i 50, 60 | |
| | | 720p 50,60 | |
| | CVBS | NTSC / PAL | |
| | HDMI | 1080p 24,25,30 | |
| | | 1080i 50, 60 | |
| | | 720p 50,60 | |
| | | 480i, 576p | |
| | | 576i, 576p | |
| | VGA | 1280x1024 60,75 | |
| | | 1280x960 60,85 | |
| | | 1152x864 75 | |
| | | 1024x768 60,70,75,85 | |
| | | 800x600 60,72,75,85 | |
| LCD | LCD | 10.05", 1280x800 RGB. | |
| Storage | SD/SDHC | Default. SANDISK 32GB (Class 10) | |
| Storage | FAT | FAT16, FAT32 (Recommended) | |
| File System | 1741 | | |
| Recording | VIDEO | AVI (H.264) | |
| File Format | VIDEO | | |
| AUDIO | AUDIO | Only HD-SDI & HDMI (Support 48KHz,16bit audio bandwidth | |
| | Speaker | 8 ohms 0.5W (Audio OUT) | |
| | Phone jack | 3.5inch Stereo (Audio OUT) | |
| Size | 266(W) x 176(H) x 38(D) | | |

DIMENSIONS




••• The multi format input monitor, which is the best for office demo, HD SDI camera test and evaluation, customer demo and exhibition or field monitor for installation of the HD SDI camera.





All information of the camera come in sight

The video input, power connection and audio input etc, kinds of video connected inforations are shown by the OSD (On Screen Display).



A handy OSD menu

In the OSD menu, display setting, adjust audio volume, system of the product, and also possible to upgrade of the new firmware in the system.



RAPPORT-10HD PRO, Support DVR function





- ① Power LED
- ② Indicate charging status
- ③ Power ON/OFF button.
- 4 Selection menu
- (5) Move and select menu.
- **6** MENU button
- 7 MODE button
- ® REC button