

Lite

960H

View



Feature

- 2HDD Bay (or 1 HDD Bay & 1 eSATA)
- Multi-Languages Supported
- Privacy Zone
- Covert Channel
- Watermarking
- Two-way Audio
- DDNS, DHCP, UPnP

Distinctive Features

- End of Line Resistor Sensor
- Dual 485 Port
- Coaxitron
- Equalizer
- Camera Tamper Alarm
- POS/ATM
- iSCSI (Recording)

General

- OS: Embedded Linux
- Compression: H.264
- Power Supply: 12V/5A - Level 5
- Consumption: 60/40Watts
- Operating Temp: 5 ~ 40°C
- Humidity: 10 ~ 80%
- Net Weight (w/o HDD): 3Kg
- Certification: CE, FCC, RoHS Compliance

Network Software

- VMS, RMS

- Mac Viewer



- Smartphone Viewer




Dimensions

- Size - 340x59x300mm

- Front



- Top



Specifications

960H

Model Name		SHI-16	SHI-08	SHI-04
System	Time Sync.	NTP, GMT, DST		
	User	15 Users (Admin., User1 ~ User14)		
Video	Input	16 BNC	8 BNC	4 BNC
	Output	1 HDMI, 1 VGA, 1 BNC		
	Spot	1 BNC - Multi-channel (16/9/4/1)		
Audio	Input	16 RCA	8 RCA	4 RCA
	Output	HDMI, RCA		
Video Recording	Speed	Realtime (max. 30fps/ch)		
	Resolution	960H (960x480/576)		
	Quality	5 Levels		
	Bit Rate	Max. 8Mbps/Ch		
Audio Rec	Compression	G.711U		
Network	Interface	Ethernet 10/100/1G		
	Compression	H.264		
	Speed	Max. CIF 8fps/ch		
	Resolution	Max. 960H		
Alarm	Post-Alarm	5sec~5min		
	Motion Grid	16x12 (NTSC/PAL)		
	Alarm Action	E-mail, Ch Popup, Buzzer, Relay, PTZ Preset, Spot, Remote VMS, Front LED		
	Input / Output	16/ 4- NC/NO/EOL	8/2 - NC/NO/EOL	4/1 - NC/NO/EOL
Display	HDMI ,VGA	Full HD, XGA		
	TV	SDTV (720x480/576)		
External Interface	PTZ / Keyboard	2 RS485 - Terminal Block		
	ATM / POS	RS232C - Terminal Block, Ethernet POS		
Storage	Primary / External / ODD	2 HDD (or 1 HDD & 1 eSATA)		



SHI-16



SHI-08



SHI-04

Blue

960H

View



Features



- 3HDD Bay
- DVD R/W
- Digital Zoom
- DDNS, DHCP, UPnP
- Multi-Languages Supported
- Privacy Zone
- Covert Channel
- Two-way Audio

Distinctive Features

- RAID1/5 (Optional)
- End of Line Resistor Sensor
- Dual 485 Port
- Coaxitron
- Equalizer
- Camera Tamper Alarm
- POS
- iSCSI
- 1x eSATA

General

- OS: Embedded Linux
- Compression: H.264
- Power Supply: 12V/5A - Level 5
- Consumption: 60Watts
- Operating Temp: 5 ~ 40°C
- Humidity: 10 ~ 80%
- Net Weight (w/o HDD): 4Kg
- Certification: CE, FCC, RoHS Compliance

Network Software

- VMS, RMS

- Mac Viewer




- Smartphone Viewer




Dimensions

- Size - 430x86x270 mm

- Front



- Top



Specifications

960H

Model Name		MHI-16	MHI-08	MHI-04
System	Time Sync.	NTP, GMT, DST		
	User	15 Users (Admin., User1 ~ User14)		
Video	Input	16 BNC	8 BNC	4 BNC
	Output	1 HDMI, 1 VGA, 1 BNC		
	Loop	16 BNC	8 BNC	4 BNC
	Spot	1 BNC - Multi-channel (16/9/4/1)		
Audio	Input	16 RCA	8 RCA	4 RCA
	Output	HDMI, RCA		
Video Recording	Speed	Realtime (max. 30fps/ch)		
	Resolution	960H (960x480/576)		
	Quality	5 Levels		
	Bit Rate	Max. 8Mbps/Ch		
Audio Rec	Compression	G.711U		
Network	Interface	Ethernet 10/100/1G		
	Compression	H.264		
	Speed	Max. CIF 8fps/ch		
	Resolution	Max. 960H		
Alarm	Post-Alarm	5sec~5min		
	Motion Grid	16x12 (NTSC/PAL)		
	Alarm Action	E-mail, Ch Popup, Buzzer, Relay, PTZ Preset, Spot, , Remote VMS, Front LED		
	Input / Output	16/4 - NC/NO/EOL	8/2 - NC/NO/EOL	4/1 - NC/NO/EOL
Display	HDMI ,VGA	Full HD, XGA		
	TV	SDTV (720x480/576)		
External Interface	PTZ / Keyboard	2 RS485 - Terminal Block		
	ATM / POS	RS232C - Terminal Block / Ethernet POS		
Storage	Primary / External / ODD	3 HDD, 1 eSATA, 1 DVD		



MHI-16



MHI-08



MHI-04

Deluxe

960H

View



Features



· 6HDD Bay



· DVD R/W



· Digital Zoom

· Jog Shuttle

· DDNS, DHCP, UPnP

· Multi-Languages Supported

· Privacy Zone

· Covert Channel

· Two-way Audio

Distinctive Features

- RAID1/5 (Optional)
- End of Line Resistor Sensor
- Dual 485 Port
- Coaxtron
- Equalizer
- Camera Tamper Alarm
- POS
- iSCSI (Recording)
- 2x eSATA

General

- OS: Embedded Linux
- Compression: H.264
- Power Supply: 90~250V, 50/60Hz
- Consumption: 80Watts
- Operating Temp: 5 ~ 40°C
- Humidity: 10 ~ 80%
- Net Weight (w/o HDD): 8Kg
- Certification: CE, FCC, RoHS Compliance

Network Software

· VMS, RMS

· Mac Viewer



· Smartphone Viewer




Dimensions

· Size - 440x88x430mm



· Top



Specifications

960H

Model Name		HD1-16
System	Time Sync.	NTP, GMT, DST
	User	15 Users (Admin., User1 ~ User14)
Video	Input	16 BNC
	Output	1 HDMI, 1 VGA, 1 BNC
	Loop	16 BNC
	Spot	1 BNC - Multi-channel (16/9/4/1)
Audio	Input	16 RCA
	Output	HDMI, RCA
Video Recording	Speed	Realtime (Max. 30fps/ch)
	Resolution	960H (960x480/576)
	Quality	5 Levels
Audio Rec	Compression	G.711U
Network	Interface	Ethernet 10/100/1G
	Compression	H.264
	Speed	Max. CIF 8fps/ch
	Resolution	Max. 960H
Alarm	Pre/Post-Alarm	5sec / 5sec~5min
	Motion Grid	16x12 (NTSC/PAL)
	Alarm Action	E-mail, Ch Popup, Buzzer, Relay, PTZ Preset, Spot, Remote VMS, Front LED
	Input / Output	16/4 - NC/NO/EOL
Display	HDMI ,VGA	Full HD, XGA
	TV	SDTV (720x480/576)
External Interface	PTZ / Keyboard	2 RS485 - Terminal Block
	ATM / POS	RS232C - Terminal Block / Ethernet POS
Storage	Primary / External / ODD	6 HDD, 2 eSATA, 1 DVD



HD1-16